



GOLDEN PRINCE



Technical Specifications

Tipper Truck	Brand	SINOTRUK
	Model	GOLDEN PRINCE
	Driving type	6x4
Cabin	Type	L2000(RHD)
	Configuration	Seatbelt for driver and co-driver, Fire extinguisher, Mp3 radio, USB, without AC
	Seating Capacity	2 seats with single bunk
Engine	Model	WD615.92NE
	Type	6 cylinders in line, 4 strokes direct injection diesel engine, water cooling, Intercooler Turbocharged with EVB
	Displacement(L)	9.726L
	Norms	EURO III
	Number of Cylinder	6
	Bore×Stroke(mm)	126×130
	Max. Power(HP/rpm)	266HP(196kw)/2200
	Max. Torque(N.m/rpm)	1100/1100-1600
Clutch	Model	Single dry plate dry coil-spring clutch, Hydraulically operating with air assistance, Diameter : 430mm clutch
Transmission	Model	HW15710
	Type	10 forward speeds, 2 reverse speeds
	Max Torque (Nm/RPM)	1500/2600
Axle	Front Axle	9 tons
	Rear Axle	2x16 tons (planetary axle with hub reduction)
Steering	Type	ZF8098, Hydraulic power assistant steering
Wheels & Tires	Type	11.00R20
	Wheels Number	10+1
Electrical System	Working Voltage	24v, negative grounded
	Starter	24V, 7.5kw
	Alternator	3-phase, 28V, 2240w
	Battery Type	2x12V-165A.H
Dimension	Overall Dimensions (L×W×H) mm	7320x2496 x3300
	Wheel Base (mm)	3800+1350
	Wheel Track (front/rear)mm	2044/1850
	Overhang (Front/Rear) mm	1320/850
	Approach/Departure Angle	16°/45°
Weights	Curb Weight (kg):	10500
	GVW(kg)	41000
Performance	Max Speed (km/h)	89
	Max Gradability (%)	40
	Min Turning Radius(m)	<17m
	Min Ground Clearance(mm)	315
	Fuel Tank Capacity(L)	400 Ltr Aluminium Alloy
Body	Body Size	12 CBM
	Overall Dimensions (L×W×H) mm	5000*2300*1050
	Thickness (mm)	Bottom 12, side 6
Brake	Type	Hydropneumatic Brake via water spray
Lifting System	Type	Hydraulic cylinder front lifting



SPARK
AUTOMOTIVES

SPARK AUTOMOTIVES PVT. LTD.

1st Floor, Block 'A' Four Square Complex, Naxal Kathmandu, Nepal
Tel: +977-01-4445592, 4445593, E-mail: info@sparkventures.com.np
Website: sparkventures.com.np