

SINOTRUK



HOWO-NX

4X2 TRACTOR HEAD

euro6 



4X2 TRACTOR HEAD

TECHNICAL SPECIFICATIONS

Chassis	Brand	SINOTRUK	
	Emission	Euro VI	
	Driving type	4x2	
Cabin	Type	H77L cabin with 4 point full-floating air suspension, 2 seats with single sleeper and AC	
	Configuration	LED Screen with 4 View Camera, seatbelt, fire extinguisher, Mp3 radio, USB	
Engine	Model	MC07H.35-61	MC07.29-61
	Type	6 cylinders, 4 strokes CRDI Engine, Water cooling, Intercooler Turbocharged	
	Displacement(L)	7.36 L	6.87L
	Number of Cylinder	6	6
	Bore×stroke (mm)	108x134	108x125
	Max. power(HP/rpm)	350HP	290HP/2200 rpm
	Max. torque(N.m/rpm)	1400N.m/1200-1700 rpm	1250 N.m/ 1200-1700 rpm
Clutch	Model	Single dry plate dry coil-spring clutch,Hydraulically operating with air assistance, Dia:430mm	
Transmission	Model	HW19709XST	HW13709XSTC
	Type	9 forward speeds, 1 reverse speed	
	Max torque (Nm/RPM)	1900 N.m	1350N.m
Axle	Front axle	VGD 7.5T	VGD 7.5T
	Rear axle	MCX 16T, with double reduction and differential lock	
Brake	Type	Air Brake , ABS with Auto Slack Adjuster	
Steering	Type	Power steering, RHD	
Wheels & Tires	Type	12.00R20	
	Wheels No	6+1	
Electrical system	Working voltage	24v, negative grounded	
	Starter	24V,6.6kw	
	Alternator	28V/80A	
	Battery type	2x12V,165Ah	
Dimensions	Overall dimensions (L×W×H) mm	6175x2500x3879	
	Wheel base (mm)	3600	
	Wheel track (front) mm	2030	
	Wheel track (rear) mm	1860	
Weights	Curb weight (kg):	6800	
	Gross Combined Weight(kg)	55000	
Performance	Max speed (km/h)	95	
	Max gradability (%)	27	
	Min ground clearance(mm)	320	
	Fuel tank capacity(L)	400	
	Urea tank Capacity(L)	45	

Note: The manufacturer reserves the right to modify the design and equipments without prior notice!

