

SINOTRUK



4X2 TRUCK CHASSIS

euro6 



4x2 TRUCK CHASSIS

TECHNICAL SPECIFICATIONS

Chassis	Brand	SINOTRUK 4x2	
	Emission	Euro VI	
	Driving type	4x2	
Cabin	Type	2080 cabin with single sleeper,3 seats with tilttable	
	Configuration	LED Screen with Backview Camera,seatbelt, fire extinguisher, Mp3 radio, USB	
Engine	Model	YCS04180-66	
	Type	4 Cylinder ,4 strokes CRDI Engine , water cooling, Intercooler Turbocharged	
	Displacement(cc)	4295	
	Number of Cylinder	4	
	Bore×stroke (mm)	105x124	
	Max. power(HP/rpm)	180Hp(132kw)@2300rpm	
Clutch	Max. torque(N.m/rpm)	650Nm@1100-1800rpm	
	Model	Single dry plate dry coil-spring clutch, Hydraulically operating with air assistance	
Transmission	Diameter(mm)	350	
	Brand/Model	8JS85TE	
	Torque (Nm)	850	
Axle	Type	8 forward speed & 2 reverse speed	
	Front axle (tons)	6T	
	Rear axle loading (tons)	13T	
Brake	Rear axle Ratio	5.8	
	Type	Air Brake , ABS with Auto Slack Adjuster	
Steering	Type	RHD, Power steering	
	Type	9.00R20	10.00R20
Wheels & Tires	Wheels number	6+1	
	Capacity(L)	16	
Urea Tank	Capacity(L)	300L, aluminium tank with locker.	
	Working voltage	24v, negative grounded	
Fuel Tanker	Starter	6.6kw/24v	
	Alternator	28V/55A	
	Battery type	2x12V-105A.H	
	Overall dimensions(mm)	7720 x 2480 x 2700	9876 x 2459 x 2569
Dimensions	Body Size	20 ft	25 ft
	Wheel base (mm)	4200	5400
	Front wheel track (mm)	1850	1879
	Rear wheel track (mm)	1860	1865
	Curb weight (kg)	4700	4900
Weights	GVW(kg)	19000	
	Max speed (km/h)	90	
Performance	Max gradability (%)	28%	
	Min Turning Radius(m)	<8	
	Min ground clearance(mm)	280	

Note: The manufacturer reserves the right to modify the design and equipments without prior notice!